


























16.08.19

F =	FLOOR											
W =	WALL											
C =	CEILING											
FU =	FURNITURE											
P =	PRODUCT											
CODE	material	application	manufacturer	type	colour	material information	surface	sample	data sheet	comment	picture	
1. floor												
by architecture												
F	Concrete	floor covering exhibition space	-	-	light grey	-	grounded	-	-	by architects		
W	Plasterboard painted	wall covering exhibition space	-	-	RAL 7035 light grey	2x layers	-	-	-	by architects		
W	Paint	C4 wall	-	-	CMYK 89 106 113 RGB 69 50 46 17 HEX #5b686d RAL 7031	2x layers	matt	-	-			
C	Acoustic ceiling	suspended ceiling exhibition space	Rockfon	Mono acoustic	panel size 900x1200mm	-	-	-	mc2_mono acoustic_rockfon	by architects		
2. floor												
by architecture												
F	Block parquet	floor covering exhibition space	-	-	brown	-	oiled	-	-	by architects		
W	Plasterboard	wall covering exhibition space	-	-	RAL 7035 light grey	2x layers	-	-	-	wall by architects		
C	Acoustic ceiling	suspended ceiling exhibition space	e.g. Troldtekt	-	-	-	-	-	-	by architects		
1. FLOOR by ATB												
LETTERCASE SHELVES MODULES (A2, A3, A4) , (C1, C2, C3) , (C5, C6, C7) , (D5, D7) , (D8, D9) , (E2, E6, E8) , (T)												
FU	Veneer Plywood/ Multiplex birch	(A2, A3, A4) , (C1, C2, C3) , (C5, C6, C7) , (D5, D7) , (D8, D9) , (E2, E6, E8) , (T) All special shelving components	-	-	birch	thickness: ~18mm, acc. to static. req.	ready to be lacquered	yes	-	with non urea-formaldehyde adhesives, Quality = I or AB or better. almost knot-free, colour inlets are possible, light. Few healthy knots are possible, but rather rare, no interfaces.		
FU	Paintable sealant/ liquid membrane barrier	(A2, A3, A4) , (C1, C2, C3) , (C5, C6, C7) , (D5, D7) , (D8, D9) , (E2, E6, E8) , (T) All plywood surfaces touching exhibits	e.g. Lubrizol or equal	e.g. Sancure or equal	none	3x coated	matt	-	-	All wood surfaces inside showcases and pedestal tops touching exhibits shall be sealed with 3 layers of either two-part epoxy or waterborne polyurethanes before painted. (oddy-Test approved)		
FU	Furniture laquer, clear	(A2, A3, A4) , (C1, C2, C3) , (C5, C6, C7) , (D5, D7) , (D8, D9) , (E2, E6, E8) , (T) All plywood surfaces	e.g. Resene Paints or equal	-	none	2x coated	matt	-	-	water based 100% acrylic paints, (VOC level should not exceed 150g/liter for non flat surfaces and 50g/liter for flat surfaces/touching exhibits). conservation-approved paint by odly-test (no oil-based)		











16.08.19

F =	FLOOR											
W =	WALL											
C =	CEILING											
FU =	FURNITURE											
P =	PRODUCT											
CODE	material	application	manufacturer	type	colour	material information	surface	sample	data sheet	comment	picture	
FU	Furniture laquer, colour	A2, A3, A4: finish of back wall in showcases	e.g. Resene Paints or equal	-	CMYK 41 12 5 0 RGB 162 199 228 HEX #a2c7e4	2x coated	Matt, low light reflection. Smooth and uniform finish.	-	-	water based 100% acrylic paints, (VOC level should not exceed 150g/liter for non flat surfaces. conservation-approved paint by oddy-test (no oil-based)		
FU	Furniture laquer, colour	C1, C2, C3: finish of back wall in showcases	e.g. Resene Paints or equal	-	CMYK 68 35 26 0 RGB 93 143 169 HEX #5d8fa9 RAL 5024	2x coated	Matt, low light reflection. Smooth and uniform finish.	-	-	water based 100% acrylic paints, (VOC level should not exceed 150g/liter for non flat surfaces. conservation-approved paint by oddy-test (no oil-based)		
FU	Furniture laquer, colour	C5, C6, C7: finish of back wall in showcases	e.g. Resene Paints or equal	-	CMYK 93 59 30 0 RGB 13 97 139 HEX #0d618b RAL 5019	2x coated	Matt, low light reflection. Smooth and uniform finish.	-	-	water based 100% acrylic paints, (VOC level should not exceed 150g/liter for non flat surfaces. conservation-approved paint by oddy-test (no oil-based)		
FU	Furniture laquer, colour	D5, D7, D8, D9: finish of back wall in showcases	e.g. Resene Paints or equal	-	CMYK 81 48 47 40 RGB 45 81 89 HEX #2d5159	2x coated	Matt, low light reflection. Smooth and uniform finish.	-	-	water based 100% acrylic paints, (VOC level should not exceed 150g/liter for non flat surfaces. conservation-approved paint by oddy-test (no oil-based)		
FU	Furniture laquer, colour	E2, E6, E8: finish of back wall in showcases	e.g. Resene Paints or equal	-	CMYK 33 0 15 26 RGB 149 180 181 HEX #95b4b5 RAL 6034	2x coated	Matt, low light reflection. Smooth and uniform finish.	-	-	water based 100% acrylic paints, (VOC level should not exceed 150g/liter for non flat surfaces. conservation-approved paint by oddy-test (no oil-based)		
FU	Steel, frame	(A2, A3, A4), (C1, C2, C3), (C5, C6, C7), (D5, D7), (D8, D9), (E2, E6, E8), (T) base for shelves	-	-	Graphite Grey RAL 7024	square steel profile, diameter ~40x40x3mm acc. to static req.	powdercoated	-	-	steel with mitre joint edges, clean and sanded welding, height adjustable feet suitable for floor (stone/concrete). Able to be cleaned with water. Anti graffiti.		
FU	Laminated safety glass	(A2, A3, A4), (C1, C2, C3), (C5, C6, C7), (D5, D7), (D8, D9), (E2, E6, E8), (T) showcases: glasses for shelving components	-	-	white glass Quality "opti white" or equal	thickness: ~10mm, acc. to static req.	-	yes	-	all glass corners to be grinded and polished well		
OR (Alternative)												
FU	Acrylic glass	(A2, A3, A4), (C1, C2, C3), (C5, C6, C7), (D5, D7), (D8, D9), (E2, E6, E8), (T) showcases: glasses for shelving components	e.g. Plexiglass or equal	e.g. UF3 or equal	clear	100% cast acrylic glass thickness: ~10mm, acc. to static req.	no anti-reflective acrylic or abrasion resistant coated acrylic.-	-	-	100% cast acrylic, durable, good clarity, no anti-reflective or abrasion resistant coated, no extruded acrylic glass		
FU	Graphic panel inside shelving unit (see trade graphic)	C1, D9 graphic panels 2x2	e.g. 3A composites or equal	e.g. Forex or equal	-	thickness: ~5mm, acc. to static req.	-	-	-	(see trade graphic)		
P	Revision bracket	invisible mounting	e.g. Häfele or equal	e.g. Keku profile or equal	-	acc. to static req.	-	-	-	-		
SPECIAL SHELF COMPONENTS												
FU	Magnetic laminate	A4: worldmap, magnetic, cutted free form mounted on plywood	e.g. Abet Laminati or equal	e.g. magnetico	ready for direct print of map illustration	Thickness: 1 mm Format: 305 x 125 cm	ready for direct print of map illustration	yes	-	-		
OR												








16.08.19

CODE	material	application	manufacturer	type	colour	material information	surface	sample	data sheet	comment	picture
FU	Magnetic metal	A4: worldmap, magnetic, cutted free form mounted on plywood	-	-	ready for direct print of map illustration	Thickness: 1 mm	ready for direct print of map illustration	-	-		
FU	Glass ESG	All Modules, Glass shelves inside Vitrine	-	-	-	white glass Quality "opti white" or equal	thickness ~8mm, acc. to static. req.	-	yes		all glass corners to be grinded and polished well
P	Rod magnet	A4: for magnetic worldmap	e.g. Calamar or equal	e.g. Neodym, N45, axial-magnetized, S-04-10-AN or equal	nickel-plated	Ø 4 mm, height 10 mm, Holding force: approx. 700 g	laquered	-	-		
P	magnification selfadhesive foil	D7: backlit Object	-	-	-	200 x 200mm	magnification 3x	-	-		
P	mortise lock for showcases	all showcases	e.g. Häfele or similar	-	-	-	-	-	-	all with same key	
PEDESTALS AND SHOWCASES											
MODULE A5, (B1, B2), B2, B3, C1, D5, D7, (D1, D7), E3 (E4, E5, E7), E4, T											
FU	Veneer Plywood/ Multiplex birch	(A0,A1), A5, (B1, B2), B2, B3, C1, D5, D7, (D1, D7), E3 (E4, E5, E7), E4, T	-	-	birch	thickness: ~18mm, acc. to static. req.	ready to be lacquered	yes		with non urea-formaldehyde adhesives, Quality = I or AB or better, almost knot-free, colour inlets are possible, light. Few healthy knots are possible, but rather rare, no interfaces.	
FU	Paintable sealant/ liquid membrane barrier	A5, (B1, B2), B2, B3, C1, D5, D7, (D1, D7), E3 (E4, E5, E7), E4, T All plywood surfaces touching exhibits	e.g. Lubrizol or equal	e.g. Sancure or equal	none	3x coated	matt	-	-	All wood surfaces inside showcases and pedestal tops touching exhibits shall be sealed with 3 layers of either two-part epoxy or waterborne polyurethanes before painted. (oddy-Test approved)	
FU	Furniture laquer, clear	(A0,A1), A5, (B1, B2), B2, B3, C1, D5, D7, (D1, D7), E3 (E4, E5, E7), E4, T All plywood surfaces	e.g. Resene Paints or equal	-	none	2x coated	matt	-	-	water based 100% acrylic paints, (VOC level should not exceed 150g/liter for non flat surfaces and 50g/liter for flat surfaces/touching exhibits). conservation-approved paint by oddy-test (no oil-based)	
FU	Steel, frame or cage	(B1, B2), B2, B3, C1, D5, D7, E3 (E4, E5, E7) cage of pedestals/showcases	-	-	Graphite Grey RAL 7024	square steel profile, diameter ~40x40x3mm acc. to static req.	powdercoated	-	-	steel with mitre joint edges, clean and sanded welding, height adjustable feet suitable for floor (stone/concrete). Able to be cleaned with water. Anti graffiti.	
FU	Laminated safety glass	A5, B2, B3, D5, D7, (D1, D7), E3 (E4, E5, E7), T showcases: glass for showcases	-	-	white glass Quality "opti white" or equal	thickness: ~10mm, acc. to static. req.	-	yes	-	all glass corners to be grinded and polished well	
OR (Alternative)											

16.08.19











F =	FLOOR											
W =	WALL											
C =	CEILING											
FU =	FURNITURE											
P =	PRODUCT											
CODE	material	application	manufacturer	type	colour	material information	surface	sample	data sheet	comment	picture	
FU	Acrylic glass	A5, B2, B3, D5, D7, (D1, D7), E3 (E4, E5, E7), T showcases: glass for showcases, table cover	e.g. Plexiglass or equal	e.g. UF3 or equal	clear	100% cast acrylic glass thickness: ~10mm, acc. to static req.	no anti-reflective acrylic or abrasion resistant coated acrylic.-	-	-	100% cast acrylic, durable, good clarity, no anti-reflective or abrasion resistant coated, no extruded acrylic glass		
P	mortris lock											
FU	Textile/Fabric	B3, E4: bench/seating fabric	e.g. Kvadrat or equal	e.g. Steelcut Trio 3	883	-	-	yes				
P	Chain with eyelet	A5, C3: book fixation	-	-	stainless steel	-	polished	-	-	fixation with stainless steel countersunk screws to furniture, fixation to book to be coordinated with client		
P	Revision bracket	invisible mounting	e.g. Häfele or equal	e.g. Keku profile or equal	-	acc. to static req.	-	-				
FU	MDF	A1: Thermochrome wall	-	-	-	thickness: ~12mm, acc. to static req.	ready to be lacquered					
FU	Thermochrome paint	A1: Thermochrome wall	e.g. SFXC or equal	e.g. Thermocromic screen printing ink or equal	acc. to ATB / MUST	2x coated	-					
WALL RAIL SYSTEM AND COMPONENTS												
RAIL SYSTEM	MODULE A5, B4,C4, C7, D1, D7, E9, F1/2											
FU	Steel, rail system	A5, C4, (B4, C7), (D1, D7), E9, F1/2: wall rails	-	-	Graphite Grey RAL 7024	square profile, diameter ~20x20x2mm, acc. to static req.	powdercoated	-	-	Able to be cleaned with water. Anti graffiti. Loadcapacity ca. 100kg/ftm		
FU	Steel-connector, reinforced angle	A5, C4, (B4, C7), (D1, D7), E9, F1/2: wall rail system connector	-	T3- Profil or similar	Graphite Grey RAL 7024	acc. To static req.	powdercoated	-	-	incl. mounting to wall		
FU	Steel-connector, reinforced angle	A5, C4, (B4, C7), (D1, D7), E9, F1/2: wall rail system connector	-	L-Profil or similar	Graphite Grey RAL 7024	acc. To static req.	powdercoated	-	-	incl. mounting to wall		
FU	Profile for component mounting, steel	A5, C4, (B4, C7), (D1, D7), E9, F1/2: component mounting to rail system	-	L-profile, U-profile	Graphite Grey RAL 7024	acc. To static req.	powdercoated	-	-			

16.08.19











F =	FLOOR											
W =	WALL											
C =	CEILING											
FU =	FURNITURE											
P =	PRODUCT											
CODE	material	application	manufacturer	type	colour	material information	surface	sample	data sheet	comment	picture	
FU	Graphic panel (by graphic trade)	A5, C4, (B4, C7), (D1, D7), E9, F1/2: graphic panel on wall rail system	e.g. 3A composites or equal	e.g. Forex or equal	acc. To graphic trade	thickness: ~5mm, acc. to static req.	-	-	-	(see graphic trade)		
FU	Acrylic glass	C4, (D1, D7), E9: glass panel and showcases on wall rail system	e.g. Plexiglass or equal	e.g. UF3 or equal	solid sheet, clear	100% cast acrylic glass thickness: ~10mm, acc. to static req.	no anti-reflective acrylic or abrasion resistant coated acrylic.-	-	-	100% cast acrylic, durable, good clarity, no anti-reflective or abrasion resistant coated, no extruded acrylic glass		
FU	Acrylic glass	C4, (D1, D7), E9: glass panel and showcases on wall rail system	e.g. Plexiglass or equal	e.g. UF3 or equal	solid sheet, white RAL 9003	100% cast acrylic glass thickness: ~10mm, acc. to static req.	no anti-reflective acrylic or abrasion resistant coated acrylic.-	-	-	100% cast acrylic, durable, no anti-reflective or abrasion resistant coated, no extruded acrylic glass		
FU	Melinex foil (by client)	C4: object fixation inside glass panel and showcases		Melinex	clear			-	-	acc. to conservatory requirements		
SPECIAL SIZES												
MODULE E1, E4												
FU	Graphic panel (by graphic trade)	E1, E4: suspension graphic panels	e.g. 3A composites or equal	e.g. Forex or equal	acc. To graphic trade	thickness: ~5mm, acc. to static req.	-	-	-	(see graphic trade)		
FU	Substructure, solid wood beam	E1, E4: suspension graphic panels	-	-	lacquered, RAL 9003 white	~50x50mm, acc. to static req.	sanded, clean ad dust free, ready to be lacquered, laquere matt	-	-	no conservation requirements		
P	Steel rope	E1, E4: Graphic panel suspension	e.g. Carl Stahl or equal	e.g. Rope with eyelet plate or equal	stainless steel	rope diamter ~ 1,2mm acc. To static req.	-	-	-			
P	Ceiling fastener with slot	E1, E4: Graphic panel suspension	e.g. Carl Stahl or equal	e.g. ceiling bracket M12x1 with thread or equal	stainless steel	~ 14x29mm, acc. To static req.	-	-	-			
MEDIA CORRIDOE / PAPER INSTALLATION												
PAPER INSTALLATION												
MODULE B												
FU	deformable acrylic glass	B: serving as substructure for paper sheets	e.g. Plexiglass or equal	-	clear	thickness: ~2.5mm, acc. to static req.	-	-	-	no conservation requirements		
FU	Printed self adhesive Vinyl	B: acrylic glass sheets; ceiling, floor	e.g. Oracal or equal	-	matt white	-	fit for digital print	-	-	Roll should be minimum 1650mm wide		
OR												
FU	Printed graphic	B: acrylic glass sheets; ceiling, floor	e.g. DuPont or equal	e.g. Tyvek or equal	white	~105g/m2	fit for digital print	yes	-	Roll should be minimum 1650mm wide		
OR												

MATERIAL | COLOUR | PRODUCT - LIST
 NORWEGIAN PRINTING MUSEUM
 STAVANGER


16.08.19

F =	FLOOR											
W =	WALL											
C =	CEILING											
FU =	FURNITURE											
P =	PRODUCT											
CODE	material	application	manufacturer	type	colour	material information	surface	sample	data sheet	comment	picture	
FU	Printed Wallpaper	B: acrylic glass sheets; ceiling, floor	e.g. Lgepa or equal	-	matt white	150g/m2 or thinner	smooth surface, fit for digital print	-	-	Roll should be minimum 1650mm wide		
P	Steel rope	B: paper installation suspension	e.g. Carl Stahl or equal	e.g. Rope with ball or equal	stainless steel	rope diameter ~ 1,2mm ball diameter ~ 3,5mm acc. To static req.	-	-	-			
P	Ceiling fastener with slot	B: paper installation suspension	e.g. Carl Stahl or equal	e.g. ceiling bracket M12x1 with thread or equal	stainless steel	~ 14x29mm, acc. To static req.	-	-	-			
MEDIA CORRIDOR												
MODULE B5												
FU	MDF	B5: media corridor wall + top	-	-	-	thickness: ~12mm, acc. to static req.	sanded, clean ad dust free, ready to be lacquered	-	-	no conservation requirements		
FU	Furniture lacquer, colour	B5: visible MDF edges	e.g. Resene Paints or equal	-	white	-	matt	-	-	no conservation requirements		
FU	Printed graphic foil (by graphic trade)	B5: media corridor wall + top + floor	e.g. Oracal or equal	-	matt white	-	fit for digital print	-	-	Roll should be minimum 1650mm wide		
OR												
FU	Printed graphic (by graphic trade)	B5: media corridor wall + top + floor	e.g. DuPont or equal	e.g. Tyvek or equal	white	~105g/m2	fit for digital print	yes	-	Roll should be minimum 1650mm wide		
OR												
FU	Printed graphic	B5: media corridor wall + top + floor	e.g. Lgepa or equal	-	matt white	150g/m2 or thinner	smooth surface, fit for digital print	-	-	Roll should be minimum 1650mm wide		
FU	Self adhesive vinyl	B5: media corridor floor	-	-	matt white	-	-	-	-	Roll should be minimum 1650mm wide, durable		
P	Revision bracket	B5: media corridor wall revision	e.g. Häfele or equal	e.g. Keku profile or equal	-	acc. to static req.	-	-	-			
2. Floor												
SEMI HIGH WALL + WALL BAR												
MODULE F												
FU	MDF	F: cover of half high room divider walls	-	-	-	thickness: ~12mm, acc. to static req.	ready to be lacquered	-	-	no conservation requirements		

16.08.19

F =	FLOOR											
W =	WALL											
C =	CEILING											
FU =	FURNITURE											
P =	PRODUCT											
CODE	material	application	manufacturer	type	colour	material information	surface	sample	data sheet	comment	picture	
FU	Furniture lacquer, colour	F: half high room divider walls	e.g. Resene Paints or equal	-	white RAL 9003	2x coated	matt	-	-	durable and scratch resistant, no conservation requirements		
FU	Reposal	F: skirting	e.g. Leitopal or equal	e.g. Melamine faced board, MDF	M1200	thickness: ~12mm, acc. to static req.	mottled	-	-			
FU	Veneer Plywood/ Multiplex birch	F: top bar of half high room divider walls, wall bar	-	-	-	thickness: ~10-15mm, acc. to static. req.	-	yes		Quality = I or AB or better. almost knot-free, colour inlets are possible, light. Few healthy knots are possible, but rather rare, no interfaces. no conservation requirements		
FU	Furniture lacquer	F: top bar of half high room divider walls, wall bar	e.g. Resene Paints or equal	-	clear	2x coated	matt	-	-	durable and scratch resistant, no conservation requirements		
FU	Steel	F: wall bar fixation	-	-	Graphite Grey RAL 7024	L profile, ~52x60x2mm, acc. To static req.	powdercoated	-	-			
MODULE F	SUSPENDED AREA TITLE											
FU	MDF	F: wood surface	-	-	-	~40x150mm, acc. to static req.	ready to be lacquered	-	-			
FU	Furniture lacquer, colour	F: surface	e.g. Resene Paints or equal	-	Anthracite Grey RAL 7016	2x coated	matt	-	-			
P	Steel rope	F: suspension	e.g. Carl Stahl or equal	e.g. Rope with eyelet plate or equal	stainless steel	rope diamter ~ 1,2mm acc. To static req.	-	-	-			
P	Ceiling fastener with slot	F: suspension	e.g. Carl Stahl or equal	e.g. ceiling bracket M12x1 with thread or equal	stainless steel	~ 14x29mm, acc. To static req.	-	-	-			
MODULE F	WORD CLOUD, TRIGGER POINT PLATE, BROCHURE HOLDER											
FU	Graphic panel (by graphic trade)	F: Graphic panel	e.g. 3A composites or equal	e.g. Forex or equal	-	thickness: ~5mm, acc. to static req.	-	-	-	(see graphic trade)		
FU	Profile for mounting components, steel	F: Graphic panel, Trigger point plate, brochure holder	-	L-profile, U-profile	Graphite Grey RAL 7024	acc. To static req.	powdercoated	-	-			
FU	Veneer Plywood/ Multiplex birch	F: Trigger point plate, brochure holder	-	-	-	thickness: ~10-15mm, acc. to static. req.	-	yes		Quality = I or AB or better. almost knot-free, colour inlets are possible, light. Few healthy knots are possible, but rather rare, no interfaces. no conservation requirements		

16.08.19

F =	FLOOR											
W =	WALL											
C =	CEILING											
FU =	FURNITURE											
P =	PRODUCT											
CODE	material	application	manufacturer	type	colour	material information	surface	sample	data sheet	comment	picture	
FU	Cast acrylic glass	B: brochure holder	e.g. Plexiglass or equal	e.g.	clear,	thickness: ~5mm, acc. to static. req., thermally formed	-	-	-	no conservation requirements		
MODULE F												
FU	Veneer Plywood/ Multiplex birch	F10: Showcase	-	-	birch	thickness: ~18mm, acc. to static. req.	ready to be lacquered	yes	-	with non urea-formaldehyde adhesives, Quality = I or AB or better. almost knot-free, colour inlets are possible, light. Few healthy knots are possible, but rather rare, no interfaces.		
FU	Paintable sealant/ liquid membrane barrier	F10: Showcase	e.g. Lubrizol or equal	e.g. Sancure or equal	none	3x coated	matt	-	-	All wood surfaces inside showcases and pedestal tops touching exhibits shall be sealed with 3 layers of either two-part epoxy or waterborne polyurethanes before painted. (oddy-Test approved)		
FU	Furniture laquer, clear	F10: Showcase	e.g. Resene Paints or equal	-	none	2x coated	matt	-	-	water based 100% acrylic paints, (VOC level should not exceed 150g/liter for non flat surfaces and 50g/liter for flat surfaces/touching exhibits). conservation-approved paint by oddy- test (no oil-based)		
FU	Laminated safety glass	(A2, A3, A4), (C1, C2, C3), (C5, C6, C7), (D5, D7), (D8, D9), (E2, E6, E8), (T) showcases: glasses for shelving components	-	-	white glass Quality "opti white" or equal	thickness: ~10mm, acc. to static. req.	-	yes	-	all glass corners to be grinded and polished well		
OR (Alternative)												
FU	Acrylic glass	(A2, A3, A4), (C1, C2, C3), (C5, C6, C7), (D5, D7), (D8, D9), (E2, E6, E8), (T) showcases: glasses for shelving components	e.g. Plexiglass or equal	e.g. UF3 or equal	clear	100% cast acrylic glass thickness: ~10mm, acc. to static. req.	no anti-reflective acrylic or abrasion resistant coated acrylic.-	-	-	100% cast acrylic, durable, good clarity, no anti- reflective or abrasion resistant coated, no extruded acrylic glass		
MODULE F												
FU	Graphic panel (by graphic trade)	F: Graphic panel	e.g. 3A composites or equal	e.g. Forex or equal	Anthracite Grey RAL 7016	thickness: ~5mm, acc. to static req.	-	-	-	(see graphic trade)		
Allowed Material touching exhibits												
MODULES: ALL												
P	Polyester Film	All Modules	eg. DuPont Teijin Films	eg. Melinex®	-	-	-	-	-	Use as protection layer touching exhibits, conservation requirements approved		
P	Low Density Polyethylene Foam	D7: backlit Object B2: Aftenblade door	eg. Plastazote®	LD 45	-	a closed cell, cross-linked polyethylene block foam	-	-	-	Use as protection layer touching exhibits, conservation requirements approved		

MATERIAL | COLOUR | PRODUCT - LIST

NORWEGIAN PRINTING MUSEUM
STAVANGER

16.08.19

F =	FLOOR											
W =	WALL											
C =	CEILING											
FU =	FURNITURE											
P =	PRODUCT											
CODE	material	application	manufacturer	type	colour	material information	surface	sample	data sheet	comment	picture	
P	Polyethylene Foams	All Modules	eg. Ethafoam™ Polyethylene Foam	-	-	-	-	-	-	Use as protection layer touching exhibits, conservation requirements approved	