

POWERNOR
Tlf.: 90 70 70 00
www.powernor.no

+K=612.0071-NB0001

CHLORIDE 80-NET 400kVA

Input Input	
U	244.6 V
V	244.6 V
W	244.6 V
	49.9 Hz

Output	
U	229.7 V
V	229.7 V
W	229.7 V
	49.8 Hz

Battery	
Voltage	655 V
Current	0.7 A
Cell Voltage	

System Status
[Green Checkmark]

Start Inverter [Green Circle] **Stop Inverter** [Red Circle] **Reset Fault** [Blue Circle] **Buzzer Mute** [Speaker Icon]

Warning/Fault **Events log** **Measures** **Battery** **LIFE** **Settings**

NLSH
82967807



EMERSON™
Network Power



48

47

46

45

44

43

42

41

40

39

38

37

36

35

34

48

47

46

45

44

43

42

41

40

39

38

37

36

35

34

48

47

46

45

44

43

42

41

40

39

38

37

36

35

34

SPENNING PÅSATT

SPENNING PÅSATT

PowerSafe®

107PSV190F

12V190F

Nominal capacity / Capacité nominale

12V 190Ah/C₁₀/1.80Vpc/20°C

12V 190Ah/C₈/1.75Vpc/77°F

Float voltage / Tensión de floating

2.280Vpc @ 20°C

2.265Vpc @ 77°F

Connection torque / Couple de serrage

9 ± 0.9 Nm - 80 ± 8 lbf in

Typical weight / Poids moyen

57.3 kg - 126.3 lbs

Non-Spillable Battery.

Made in EU



WARNING: Battery posts, terminals, and related accessories contain lead and lead compounds, chemicals known to the State of California to cause cancer and reproductive harm. Batteries also contain other chemicals known to the State of California to cause cancer.
WASH HANDS AFTER HANDLING.

WARNING: Risk of fire, explosion, or burns. Do not disassemble, heat above 60°C, or incinerate.

www.enersys.com

EnerSys

